

Test Application Form



HOHENSTEIN

Report to: Applicant/Supplier Buyer Invoice to: Applicant/Supplier Buyer

Quotation No.: If available Laboratory's Use Only: Report No.: Due Date:

Applicant/Supplier:

Applicant/Supplier Name:
Address:
Contact Person: Telephone: Cell:
E-Mail:
VAT-No Applicant:

Payer:

Payer Name:
Address:
Contact Person: Telephone: Cell:
E-Mail:
VAT-No Payer:

Information Sample Material:

Sample Description:
Composition: Country of Destination:
Colour/Category: End Use:
Style No. Order No. Article No.:
Country of Origin: End Customer/Buyer:
Re-Test: No Yes, earlier report number Self-reference: Yes No
Others:

Care Instructions:

Washing: Others: Drycleaning: Others:
Bleaching: Others: Drying: Others: Ironing:

Tests Required:

| | | |
|---|---|---|
| Dimensional Stability: <input type="checkbox"/> Washing: <input type="checkbox"/> 1 wash <input type="checkbox"/> 3 washes | Physical: <input type="checkbox"/> Tensile strength <i>DIN EN ISO 13934</i> <input type="checkbox"/> -1 (Strip) <input type="checkbox"/> -2 (Grab) <input type="checkbox"/> Tear strength <i>DIN EN ISO 13937</i> <input type="checkbox"/> -2 (Single tear) <input type="checkbox"/> -3 (Wing tear) <input type="checkbox"/> -4 (Tongue tear) <input type="checkbox"/> Seam slippage <i>ISO 13936</i> - <input type="checkbox"/> 1/ <input type="checkbox"/> 2 <input type="checkbox"/> Seam strength <i>ISO 13935</i> - <input type="checkbox"/> 1/ <input type="checkbox"/> 2 <input type="checkbox"/> Bursting strength <input type="checkbox"/> Abrasion resistance <input type="checkbox"/> Water repellency <input type="checkbox"/> Water absorption (capillary rise method) <input type="checkbox"/> Attachment strength <input type="checkbox"/> Moisture drying time <input type="checkbox"/> Thread per inch/stitch density <input type="checkbox"/> Yarn count <input type="checkbox"/> Fabric weight <input type="checkbox"/> Fibre composition <input type="checkbox"/> Zipper strength <input type="checkbox"/> Flammability <input type="checkbox"/> Stretch & recovery (elongation) <input type="checkbox"/> Care label recommendation/Verification <input type="checkbox"/> Odour <input type="checkbox"/> Corrosion resistance <input type="checkbox"/> Visual assessments <input type="checkbox"/> Pilling resistance: <input type="checkbox"/> ICI Pilling <input type="checkbox"/> Martindale <input type="checkbox"/> Random Tumble Pilling | Chemical: <input type="checkbox"/> AZO dyes <input type="checkbox"/> Aniline <input type="checkbox"/> pH value <input type="checkbox"/> Formaldehyde <input type="checkbox"/> Extractable heavy metals <input type="checkbox"/> Heavy metals (Packaging materials) <input type="checkbox"/> Chlorinated phenols PCP/TECP/OPP <input type="checkbox"/> Allergenic & carcinogenic dyes <input type="checkbox"/> Phthalates <input type="checkbox"/> Organic tin compounds <input type="checkbox"/> Chlorinated benzenes & toluene <input type="checkbox"/> AP/APEO <input type="checkbox"/> PFC <input type="checkbox"/> PAH <input type="checkbox"/> Release of nickel <input type="checkbox"/> Total cadmium <input type="checkbox"/> Total lead <input type="checkbox"/> VOC <input type="checkbox"/> PVC identification <input type="checkbox"/> DMFu <input type="checkbox"/> SCCP / MCCP <input type="checkbox"/> Bisphenol <input type="checkbox"/> Bisphenol A <input type="checkbox"/> Quinoline Test Packages: <input type="checkbox"/> OEKO-TEX® STANDARD 100 OEKO-TEX® Product Class: <input type="checkbox"/> I <input type="checkbox"/> II <input type="checkbox"/> III <input type="checkbox"/> IV OEKO-TEX® Appendix: <input type="checkbox"/> 4 <input type="checkbox"/> 6 <input type="checkbox"/> PPC |
| Dry Cleaning: <input type="checkbox"/> during steaming <input type="checkbox"/> during ironing | | |
| Appearance: <input type="checkbox"/> after washing: <input type="checkbox"/> 1 wash <input type="checkbox"/> 3 washes <input type="checkbox"/> after dry cleaning <input type="checkbox"/> wash and wear (easy/non ironing or self-smoothing) | | |
| Spirality/Twisting: <input type="checkbox"/> after washing: <input type="checkbox"/> 1 wash <input type="checkbox"/> 3 washes | | |
| Print Durability: <input type="checkbox"/> after washing: <input type="checkbox"/> 1 wash <input type="checkbox"/> 3 washes | | |
| Colour Fastness to: <input type="checkbox"/> Washing <input type="checkbox"/> Water <input type="checkbox"/> Dry cleaning <input type="checkbox"/> Rubbing/crocking <input type="checkbox"/> Perspiration <input type="checkbox"/> Artificial light: Grade <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/> Sea water <input type="checkbox"/> Swimming pool water <input type="checkbox"/> Chlorine bleach <input type="checkbox"/> Non-chlorine bleach <input type="checkbox"/> Saliva and perspiration <input type="checkbox"/> Phenolic yellowing <input type="checkbox"/> Sublimation | | |
| Others: | | |

Service Type: (Special services are only available for certain tests. Nickel release test takes 7-10 days by nature of testing.)

Regular (5-7 Working Days) Express (3-5 Working Days - 50% Surcharge) Emergency (2 Working Days - 100% Surcharge)

We request for the above tests & agree that all testing will be carried out subject to Hohenstein scale of charges as set forth in their price list of which we have seen a copy.

Date

Authorized Signature or Company Stamp